



HAULMAX TYRES®

ENGINEERED IN AUSTRALIA

HRT309

PREMIUM DRIVE

DRIVE PATTERN FOR REGIONAL APPLICATIONS

- An on/off road drive tyre designed to promote traction and even tread wear
- Large contact area for optimum traction in high torque requirements
- Tread rubber compound provides cut & chip wear resistance
- 20mm tread depth designed to resist squirm lug movement preventing premature tyre removal
- Casing with steel belt construction provides outstanding durability and retreadability



TECHNICAL SPECIFICATIONS



TYRE SIZE	PLY	TT/TL	TREAD DEPTH (mm)	REC-RIM WIDTH	LOAD INDEX	SPEED SYMBOL	TYRE DIMENSIONS (mm)	
							SW	OD
11R22.5	16PR	TL	20	8.25	148/145	M	279	1065



PHONE NOW

1300 761 802

Fax 1300 458 353

Australian Tyre Traders Pty Ltd

VICTORIA
NEW SOUTH WALES
QUEENSLAND
NORTH QUEENSLAND
SOUTH AUSTRALIA
TASMANIA

23 Sunshine Road, West Footscray, Victoria 3012
2H, Door 57, 14 Dennistoun Ave, Yennora, NSW, 2161
Fox Rd, Acacia Ridge, QLD, 4110
22-26 Jay Street, Bohle, Queensland 4814
532 Cross Keys Road, Cavan, South Australia 5094
2/7-9 Wilmot St, South Launceston, Tasmania 7249

sales@tyretraders.com.au | www.tyretraders.com.au