



# HALITRAX TYRES®

TYRES FOR THE LONG HAUL

L2 - BIAS PLY

## OTR - HALITRAX L2

### FEATURES

- Aggressive tread design with CRC compound to supply excellent abrasion, cut and chocking resistance.
- Tread compound customised for extended lifespan.
- Resistant to damage whilst still providing superior traction.

### BENEFITS

- Very high life span.
- High traction with long service on a variety of surfaces.
- More resistant to damage whilst still providing superior traction.
- Industry leading performance in Australian conditions.
- Great service on off-road applications.



### TECHNICAL SPECIFICATIONS

TYRE SIZE	PLY RATING	TREAD PATTERN	LOAD INDEX	REC RIM WIDTH	INFLATED DIMENSIONS (mm)		TREAD DEPTH (mm)	MAX LOAD CAPACITY (kg) 10KM/Hw	MAX INFLATION PRESSURE (kPa) 10KM/H
					SECTION WIDTH	OVERALL DIAMETER			
15.5-25*	12	L2 - LOM	168A2	12.00/1.5	421	1265	26	5600kg	400kPa
17.5-25**	16	L2 - LOM	177A2	14.00/1.5	465	1350	28	7300kg	475kPa

\*Suitable for single piece rim

\*\*Suitable for multi piece rim



PHONE NOW

**1300 761 802**

Fax 1300 458 353

## Australian Tyre Traders Pty Ltd

VICTORIA  
 NEW SOUTH WALES  
 QUEENSLAND  
 NORTH QUEENSLAND  
 SOUTH AUSTRALIA  
 TASMANIA

23 Sunshine Road, West Footscray, Victoria 3012  
 2H, Door 57, 14 Dennistoun Ave, Yennora, NSW, 2161  
 Fox Rd, Acacia Ridge, QLD, 4110  
 22-26 Jay Street, Bohle, Queensland 4814  
 532 Cross Keys Road, Cavan, South Australia 5094  
 2/7-9 Wilmot St, South Launceston, Tasmania 7249

sales@tyretraders.com.au | www.tyretraders.com.au