



NULUG



Features	Benefits
<ul style="list-style-type: none"> • Special transverse tread Pattern • Strong casing 	<ul style="list-style-type: none"> • Reduces stone trapping • Good traction • Durable

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
12.00-24	18	8.5	305	1240	20.5	4250@8.15	3728@7.45	578	24RR	TR 78A
12.00-20	18	8.5	300	1105	17.0	3725@8.10	3265@7.40	512	20RR	TR 78A

M - 77



Features	Benefits
<ul style="list-style-type: none"> • Rib lug tread pattern • Open & aggressive Tread design • Premium tread compound 	<ul style="list-style-type: none"> • All wheel fitment • Excellent traction • Enhanced mileage & Cut resistance

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
8.25-20	14	6.5	240	1000	19.0	2230@8.15	1960@7.40	472	20M	TR 175A
9.00-20	14	7.0	265	1050	21.4	2570@7.35	2255@7.15	490	20N	TR 175A
9.00-20	16	7.0	275	1060	21.5	2650@8.15	2325@7.4	496	20N	TR 175A
10.00-20	16	7.5	270	1070	21.6	3000@7.85	2630@7.40	504	20N	TR 78A
11.00-20	16	8.0	295	1100	21.6	3265@8.10	2865@7.40	520	20RR	TR 78A
12.00-20	18	8.5	315	1170	21.6	3725@8.10	3265@7.40	528	20RR	TR 78A
12.00-24	18	8.5	310	1245	22.0	4250@8.15	3728@7.45	583	24RR	TR 78A